

strapex

SMG 65

**High performance machine
for plastic strapping**




For large and heavy packages

SMG 65

Cost effective, efficient Easy operation

Highlights

Easy operation	Touch Panel Easy fault clearance without tools
High availability	Secure strap guide thanks to exclusive closed strap guide system
Flexibel	For integration into conveyor systems or as stand alone machine with non-driven rollers



Strap tension easily adjustable with press button




Simple coil change



Easily accessible, maintenance without tools

Strapex advantage



Machine, strap and after-sales service as a total package



Options
Adaptable to different operating conditions and requirements



Strap for cost effective strapping
Use of thin PP strap

Technical data

Cycles per minute, up to	65
Arch dimension (width x height)	from: 650 x 500 mm
Seal height	560–1040 mm
Electrical supply	230 V, 50 Hz 115 V, 60 Hz

Strap tension	
– with manual feed, up to	450 N
– with automatic feed (Option), up to	600 N
Emission sound pressure level	79 dB (A)
Weight, from	190 kg

Plastic strap: Polypropylene (PP)	
9 mm	371.609.545
12 mm	371.612.533
Strap coil, inside/outside Ø	200/430 mm

Packages	
Min. width x height	50 x 100 mm
Package weight, max.	50 kg*

*Depending on the conveyor technology



Make your products feel safe

www.strapex.com